

# 充実した商品ラインアップ 全43機種

用途	形名	接続 パイプ (mm)	タイプ	風量 (m³/h) ※風量は開放時																		
				50	75	100	125	150	175	200	250	300	400	500	600	700	800	900				
天井埋込形	1部屋用	φ75	07	VD-07ZVC <sub>7</sub> *1	50																	
				VD-10ZVC <sub>7</sub> 、VD-10ZVEC <sub>7</sub> -FP、VD-10ZAVC <sub>7</sub> *1 (人感センサー付)	10	60	100															
					13	75	120															
				VD-15ZVC <sub>7</sub>	φ100	15	VD-13ZVC <sub>7</sub> 、VD-13ZVEC <sub>7</sub> -FP、VD-13ZAVC <sub>7</sub> *1 (人感センサー付)	85	160	280												
							VD-18ZSVC <sub>7</sub>	100	180	320												
							VD-18ZASVC <sub>7</sub> *1 (人感センサー付)	120	200													
				2~3部屋用	φ150	18	VD-18ZVC <sub>7</sub>	180	300	430												
	VD-20ZVC <sub>7</sub>	230	340				550															
	VD-20ZAVC <sub>7</sub> *1 (人感センサー付)	230	380																			
	VD-23ZVB <sub>6</sub>	280	480				800															
	台所用	φ100	10	VD-10ZFVC <sub>7</sub>	75	120																
				φ100	15	VD-15ZFVC <sub>7</sub>	85	160	280													
						18	100	180	320													
		φ150	20	VD-13ZVY <sub>7</sub>	75	120																
VD-15ZVY <sub>7</sub>				85	160	280																
VD-18ZV <sub>6</sub>				180	300	430																
VD-20ZV <sub>6</sub>				230	340	550																
1部屋用		φ200	25	VD-23ZV <sub>6</sub>	330	480	850															
				φ150	15	VD-15ZVX <sub>7</sub> -C、-FP	85	160	280													
						18	130	180	300	430												
	φ150			20	VD-18ZAGVR <sub>7</sub> -C	170	230	340	550													
					VD-20ZVX <sub>7</sub> -C、-FP、VD-20ZVE <sub>7</sub> -FP	260	370	600														
					VD-20ZAGVR <sub>7</sub> -C	260	300	400	500	600												
	φ200			25	VD-20ZVR <sub>7</sub> -C*3	100	150	200	250	300	400	500	600									
VD-23ZVX <sub>6</sub> -C、-FP、VD-23ZVE <sub>6</sub> -FP		260	460		800																	
中間取付形	φ150	20	※2	VD-25ZVX <sub>6</sub> -C、-FP、VD-25ZVE <sub>6</sub> -FP	360	650	900															
				φ100	13	V-13ZMVC <sub>3</sub>	70	100														
						φ100	15	V-15ZMVC <sub>3</sub>	80	120	275											
								18	130	170	350											

- 弱運転時の風量 (定風量制御)
- 強運転時の風量 (定風量制御)
- 急速運転時の風量
- 急速運転時の風量 (定風量制御)

※1:浴室使用不可 ※2:事務所・施設・店舗用 ※3:24時間換気(弱):5段階、強:3段階からそれぞれ風量設定が可能。