Mitsubishi Electric AC Servo System

Sales and Service

No.21-13AE

Addition of Combinations of HG Series Servo Motors and MR-J5 Series AC Servo Amplifiers

Thank you for your continued patronage of the Mitsubishi Electric AC servo system.

The MR-J5 series AC servo amplifiers will support the HG series servo motors.

New functions of the MR-J5 can be used without replacing the existing servo motors used with the MR-J4, improving the performance and functions of the system.

1. Target Model

MR-J5 series 1-axis servo amplifiers MR-J5-G/MR-J5-G-N1/MR-J5-A/MR-J5-B (200 V)

2. Servo amplifier/servo motor combinations

The HG series servo motors supported by the MR-J5 series 1-axis servo amplifiers (200 V) are shown in Table 1.

Table 1. Servo amplifier/ser	o motor combinations *1
------------------------------	-------------------------

	MR-J5 1-axis servo amplifier (200 V)										
Servo	Servo motor *2		20G	40G	60G	70G	100G	200G	350G	500G	700G
00170			20A	40A	60A	70A	100A	200A	350A	500A	700A
			20B	40B	60B	70B	100B	200B	350B	500B	700B
	HG-KR053	0	-	-	-	-	-	-	-	-	-
	HG-KR13	0	1	-	-	-	-	-	-	-	-
HG-KR	HG-KR23	-	0	-	-	-	-	-	-	-	-
	HG-KR43	-	-	0	-	-	-	-	-	-	-
	HG-KR73	-	-	-	-	0	-	-	-	-	-
	HG-MR053	0	-	-	-	-	-	-	-	-	-
	HG-MR13	0	-	-	-	-	-	-	-	-	-
HG-MR	HG-MR23	1	0	-	-	-	-	-	-	-	-
	HG-MR43	-	-	0	-	-	-	-	-	-	-
	HG-MR73	-	-	-	-	0	-	-	-	-	-
	HG-SR52	1	1	-	0	-	-	-	-	-	-
	HG-SR102	-	-	-	-	-	0	-	-	-	-
HG-SR	HG-SR152	-	-	-	-	-	-	0	-	-	-
	HG-SR202	-	-	-	-	-	-	0	-	-	-
	HG-SR352	-	-	-	-	-	-	-	0	-	-
	HG-SR502	-	-	-	-	-	-	-	-	0	-
	HG-SR702	-	-	-	-	-	-	-	-	-	0

^{*1.} Torque characteristics of combinations with MR-J5 servo amplifiers are the same as those of combinations with MR-J4 servo amplifiers. Note that the torque cannot be increased with the combinations in Table 1.

3. Usage

To use the MR-J5 servo amplifiers with the HG series servo motors, servo amplifier parameter settings are necessary. For details, contact your local sales office.

Date	July 2021	Servo Motors and MR-J5 Series	Mitsubishi Electric Corp., Nagoya Works
of	(Revision:		1-14, Yada-minami 5-chome, Higashi-ku, Nagoya 461-8670
issue	May 2022)		Tel.: +81 (52) 721-2111 Main line

^{*2.} Servo motors with an electromagnetic brake, oil seal, keyed shaft, and D-cut shaft and geared servo motors are also supported.

4. Supported Servo Amplifier Version

(1) MR-J5-G, MR-J5-G-N1, MR-J5-A

The combinations can be used on servo amplifiers with firmware version C0 or later. This change will be made sequentially from the June 2021 production.

(2) MR-J5-B
The combinations are supported from the initial firmware version.

Revisions

Version	Date of issue	Revision	
Α	May 2022	MR-J5-B has been added along with the release.	