

**Change in the Power Supply Specifications of the LM-10WA-CCL Tension Meter**

## ■Date of Issue

December 2025

## ■Relevant Models

Tension controllers

Thank you for your continued support of Mitsubishi Electric tension controllers.

We are informing you that the inrush current specifications of the LM-10WA-CCL tension meter will be changed.  
Other general specifications, performance specifications, functions, and external dimensions remain unchanged.

**1 RELEVANT MODEL**

Product	Model
Tension meter	LM-10WA-CCL

**2 DETAILS ON THE CHANGE**

The inrush current specifications of the LM-10WA-CCL tension meter will be changed as follows.

Item	Before	After
Inrush current	Up to 20A, 2ms	Up to 30A, for 2ms or less/24VDC

**3 REASON FOR THE CHANGE**

Due to parts replacement to ensure stable product supply

**4 SCHEDULE**

The change will apply to the products to be manufactured in January 2026 and later.

There may be cases where products before the change and after the change exist in the distribution stage.

CT-A-0022-A

---

**REVISIONS**

Version	Date of issue	Revision
A	December 2025	First edition

**TRADEMARKS**

The company names, system names and product names mentioned in this technical bulletin are either registered trademarks or trademarks of their respective companies.

In some cases, trademark symbols such as '™' or '®' are not specified in this technical bulletin.