





設置 形態	タイプ名	電圧	形名	住宅用換気 システム 設計ソフト 対象機種※1	希望小売 価格 (税別)	風量(強)	対象 床面積 (目安)※2	消費電力	熱交換効率 ※3		CO2 センサー 対応可否 ※4	サイズ			接続 パイプ	アレル 除去 フィルター 対応可否	備考
									温度	冷房(エンタルピー)		高さ	幅	奥行			
天井 埋込	業務用ロスナイ天井埋込形 DCマイコン	100/200V	LGH-N15RXW	○ 障害内	¥209,000	150m ³ /h	15.0m ²	75.0W	74.0%	64.5%	○ 当社別売	290mm	810mm	780mm	Φ100mm	○ 当社別売	
		100/200V	LGH-N25RXW	○ 障害内	¥229,000	250m ³ /h	25.0m ²	100.0W	70.0%	63.0%	○ 当社別売	290mm	735mm	780mm	Φ150mm	○ 当社別売	
		100/200V	LGH-N35RXW	○ 障害内	¥252,000	350m ³ /h	35.0m ²	140.0W	71.5%	65.5%	○ 当社別売	330mm	875mm	890mm	Φ150mm	○ 当社別売	
		100/200V	LGH-N50RXW	○ 障害内	¥310,000	500m ³ /h	50.0m ²	215.0W	71.0%	63.0%	○ 当社別売	330mm	1,020mm	890mm	Φ200mm	○ 当社別売	
		100/200V	LGH-N65RXW	○ 障害内	¥415,000	650m ³ /h	65.0m ²	355.0W	71.5%	63.0%	○ 当社別売	404mm	892mm	984mm	Φ200mm	○ 当社別売	
		100V	LGH-N80RXV	○ 障害内	¥495,000	800m ³ /h	80.0m ²	420.0W	73.0%	65.0%	○ 当社別売	404mm	1,004mm	1,144mm	Φ250mm	○ 当社別売	
		100V	LGH-N100RXV	○ 障害内	¥495,000	1,000m ³ /h	100.0m ²	515.0W	73.0%	65.0%	○ 当社別売	404mm	1,231mm	1,144mm	Φ250mm	○ 当社別売	
		200V	LGH-N80RXVD	○ 障害内	¥564,000	800m ³ /h	80.0m ²	420.0W	73.0%	65.0%	○ 当社別売	404mm	1,004mm	1,144mm	Φ250mm	○ 当社別売	
		200V	LGH-N100RXVD	○ 障害内	¥564,000	1,000m ³ /h	100.0m ²	515.0W	73.0%	65.0%	○ 当社別売	404mm	1,231mm	1,144mm	Φ250mm	○ 当社別売	
		200V	LGH-N150RXVD	×	¥990,000	1,500m ³ /h	150.0m ²	850.0W	74.0%	66.0%	○ 当社別売	808mm	1,004mm	1,144mm	Φ250mm	○ 当社別売	接続パイプ(室外側)は角270°×700
		200V	LGH-N200RXVD	×	¥1,128,000	2,000m ³ /h	200.0m ²	1,030.0W	73.0%	65.0%	○ 当社別売	808mm	1,231mm	1,144mm	Φ250mm	○ 当社別売	接続パイプ(室外側)は角270°×700
	業務用ロスナイ天井埋込形 DCマイコン (CO ₂ センサー付き)	100/200V	LGH-N15RXW-C	○ 障害内	¥377,000	150m ³ /h	15.0m ²	75.0W	74.0%	64.5%	◎ 標準搭載	290mm	898mm	853mm	Φ100mm	○ 当社別売	
		100/200V	LGH-N25RXW-C	○ 障害内	¥397,000	250m ³ /h	25.0m ²	100.0W	70.0%	63.0%	◎ 標準搭載	290mm	918mm	988mm	Φ150mm	○ 当社別売	
		100/200V	LGH-N35RXW-C	○ 障害内	¥420,000	350m ³ /h	35.0m ²	140.0W	71.5%	65.5%	◎ 標準搭載	330mm	1,028mm	1,128mm	Φ150mm	○ 当社別売	
		100/200V	LGH-N50RXW-C	○ 障害内	¥478,000	500m ³ /h	50.0m ²	215.0W	71.0%	63.0%	◎ 標準搭載	330mm	1,058mm	1,288mm	Φ200mm	○ 当社別売	
		100/200V	LGH-N65RXW-C	○ 障害内	¥583,000	650m ³ /h	65.0m ²	355.0W	71.5%	63.0%	◎ 標準搭載	404mm	1,152mm	1,160mm	Φ200mm	○ 当社別売	
		100V	LGH-N80RXV-C	○ 障害内	¥663,000	800m ³ /h	80.0m ²	420.0W	73.0%	65.0%	◎ 標準搭載	404mm	1,312mm	1,272mm	Φ250mm	○ 当社別売	
		100V	LGH-N100RXV-C	○ 障害内	¥732,000	1,000m ³ /h	100.0m ²	515.0W	73.0%	65.0%	◎ 標準搭載	404mm	1,312mm	1,499mm	Φ250mm	○ 当社別売	
		200V	LGH-N80RXVD-C	○ 障害内	¥663,000	800m ³ /h	80.0m ²	420.0W	73.0%	65.0%	◎ 標準搭載	404mm	1,312mm	1,272mm	Φ250mm	○ 当社別売	
		200V	LGH-N100RXVD-C	○ 障害内	¥732,000	1,000m ³ /h	100.0m ²	515.0W	73.0%	65.0%	◎ 標準搭載	404mm	1,312mm	1,499mm	Φ250mm	○ 当社別売	
		200V	LGH-N150RXVD-C	×	¥1,158,000	1,500m ³ /h	150.0m ²	850.0W	74.0%	66.0%	◎ 標準搭載	808mm	1,277mm	1,272mm	Φ250mm	○ 当社別売	接続パイプ(室外側)は角270°×700
		200V	LGH-N200RXVD-C	×	¥1,296,000	2,000m ³ /h	200.0m ²	1,030.0W	73.0%	65.0%	◎ 標準搭載	808mm	1,277mm	1,499mm	Φ250mm	○ 当社別売	接続パイプ(室外側)は角270°×700
天井 埋込	業務用ロスナイ天井埋込形 DCリブレースマイコン	100V	LGH-RN15RXV	○ 障害内	¥219,000	150m ³ /h	15.0m ²	75.0W	74.0%	64.5%	○ 当社別売	290mm	898mm	875mm	Φ100mm	○ 当社別売	
		100V	LGH-RN25RXV	○ 障害内	¥240,000	250m ³ /h	25.0m ²	100.0W	70.0%	63.0%	○ 当社別売	290mm	918mm	1,000mm	Φ150mm	○ 当社別売	
		100V	LGH-RN35RXV	○ 障害内	¥265,000	350m ³ /h	35.0m ²	140.0W	71.5%	65.5%	○ 当社別売	330mm	1,028mm	1,140mm	Φ150mm	○ 当社別売	
		100V	LGH-RN50RXV	○ 障害内	¥326,000	500m ³ /h	50.0m ²	215.0W	71.0%	63.0%	○ 当社別売	330mm	1,058mm	1,285mm	Φ200mm	○ 当社別売	
		100V	LGH-RN65RXV	○ 障害内	¥436,000	650m ³ /h	65.0m ²	355.0W	71.5%	63.0%	○ 当社別売	404mm	1,152mm	1,157mm	Φ200mm	○ 当社別売	
		100V	LGH-RN80RXV	○ 障害内	¥520,000	800m ³ /h	80.0m ²	420.0W	73.0%	65.0%	○ 当社別売	404mm	1,312mm	1,269mm	Φ250mm	○ 当社別売	
		100V	LGH-RN100RXV	○ 障害内	¥592,000	1,000m ³ /h	100.0m ²	515.0W	73.0%	65.0%	○ 当社別売	404mm	1,312mm	1,496mm	Φ250mm	○ 当社別売	
		200V	LGH-RN15RXVD	○ 障害内	¥219,000	150m ³ /h	15.0m ²	75.0W	74.0%	64.5%	○ 当社別売	290mm	898mm	875mm	Φ100mm	○ 当社別売	
		200V	LGH-RN25RXVD	○ 障害内	¥240,000	250m ³ /h	25.0m ²	100.0W	70.0%	63.0%	○ 当社別売	290mm	918mm	1,000mm	Φ150mm	○ 当社別売	
		200V	LGH-RN35RXVD	○ 障害内	¥265,000	350m ³ /h	35.0m ²	140.0W	71.5%	65.5%	○ 当社別売	330mm	1,028mm	1,140mm	Φ150mm	○ 当社別売	
	業務用ロスナイ天井埋込形 DCリブレースマイコン (CO ₂ センサー付き)	200V	LGH-RN50RXVD	○ 障害内	¥326,000	500m ³ /h	50.0m ²	215.0W	71.0%	63.0%	○ 当社別売	330mm	1,058mm	1,285mm	Φ200mm	○ 当社別売	
		200V	LGH-RN65RXVD	○ 障害内	¥436,000	650m ³ /h	65.0m ²	355.0W	71.5%	63.0%	○ 当社別売	404mm	1,152mm	1,157mm	Φ200mm	○ 当社別売	
		200V	LGH-RN80RXVD	○ 障害内	¥520,000	800m ³ /h	80.0m ²	420.0W	73.0%	65.0%	○ 当社別売	404mm	1,312mm	1,269mm	Φ250mm	○ 当社別売	
		200V	LGH-RN100RXVD	○ 障害内	¥592,000	1,000m ³ /h	100.0m ²	515.0W	73.0%	65.0%	○ 当社別売	404mm	1,312mm	1,496mm	Φ250mm	○ 当社別売	
		200V	LGH-RN150RXVD	×	¥1,040,000	1,500m ³ /h	150.0m ²	850.0W	74.0%	66.0%	○ 当社別売	808mm	1,277mm	1,249mm	Φ250mm	○ 当社別売	接続パイプ(室外側)は角270°×700
		200V	LGH-RN200RXVD	×	¥1,184,000	2,000m ³ /h	200.0m ²	1,030.0W	73.0%	65.0%	○ 当社別売	808mm	1,277mm	1,476mm	Φ250mm	○ 当社別売	接続パイプ(室外側)は角270°×700
		100V	LGH-RN15RXV-C	○ 障害内	¥387,000	150m ³ /h	15.0m ²	75.0W	74.0%	64.5%	◎ 標準搭載	290mm	898mm	853mm	Φ100mm	○ 当社別売	
		100V	LGH-RN25RXV-C	○ 障害内	¥408,000	250m ³ /h	25.0m ²	100.0W	70.0%	63.0%	◎ 標準搭載	290mm	918mm	988mm	Φ150mm	○ 当社別売	
		100V	LGH-RN35RXV-C	○ 障害内	¥433,000	350m ³ /h	35.0m ²	140.0W	71.5%	65.5%	◎ 標準搭載	330mm	1,028mm	1,128mm	Φ150mm	○ 当社別売	
		100V	LGH-RN50RXV-C	○ 障害内	¥494,000	500m ³ /h	50.0m ²	215.0W	71.0%	63.0%	◎ 標準搭載	330mm	1,058mm	1,288mm	Φ200mm	○ 当社別売	
		100V	LGH-RN65RXV-C	○ 障害内	¥604,000	650m ³ /h	65.0m ²	355.0W	71.5%	63.0%	◎ 標準搭載	404mm	1,152mm	1,160mm	Φ200mm	○ 当社別売	
天井 埋込	業務用ロスナイ天井埋込形 DCリブレースマイコン (CO ₂ センサー付き)	100V	LGH-RN80RXV-C	○ 障害内	¥688,000	800m ³ /h	80.0m ²	420.0W	73.0%	65.0%	◎ 標準搭載	404mm	1,312mm	1,272mm	Φ250mm	○ 当社別売	
		100V	LGH-RN100RXV-C	○ 障害内	¥760,000	1,000m ³ /h	100.0m ²	515.0W	73.0%	65.0%	◎ 標準搭載	404mm	1,312mm	1,499mm	Φ250mm	○ 当社別売	
		200V	LGH-RN15RXVD-C	○ 障害内	¥387,000	150m ³ /h	15.0m ²	75.0W	74.0%	64.5%	◎ 標準搭載	290mm	898mm	853mm	Φ100mm	○ 当社別売	
		200V	LGH-RN25RXVD-C	○ 障害内	¥408,000	250m ³ /h	25.0m ²	100.0W	70.0%	63.0%	◎ 標準搭載	290mm	918mm	988mm	Φ150mm	○ 当社別売	
		200V	LGH-RN35RXVD-C	○ 障害内	¥433,000	350m ³ /h	35.0m ²	140.0W	71.5%	65.5%	◎ 標準搭載	330mm	1,028mm	1,128mm	Φ150mm	○ 当社別売	
		200V	LGH-RN50RXVD-C	○ 障害内	¥494,000	500m ³ /h	50.0m ²	215.0W	71.0%	63.0%	◎ 標準搭載	330mm	1,058mm	1,288mm	Φ200mm	○ 当社別売	
		200V	LGH-RN65RXVD-C	○ 障害内	¥604,000	650m ³ /h	65.0m ²	355.0W	71.5%	63.0%	◎ 標準搭載	404mm	1,152mm	1,160mm	Φ200mm	○ 当社別売	
		200V	LGH-RN80RXVD-C	○ 障害内	¥688,000	800m ³ /h	80.0m ²	420.0W	73.0%	65.0%	◎ 標準搭載	404mm	1,312mm	1,272mm	Φ250mm	○ 当社別売	
		200V	LGH-RN100RXVD-C	○ 障害内	¥760,000	1,000m ³ /h	100.0m ²	515.0W	73.0%	65.0%	◎ 標準搭載	404mm	1,312mm	1,499mm	Φ250mm	○ 当社別売	
		200V	LGH-RN150RXVD-C	×	¥1,208,000	1,500m ³ /h	150.0m ²	850.0W	74.0%	66.0%	◎ 標準搭載	808mm	1,277mm	1,272mm	Φ250mm	○ 当社別売	接続パイプ(室外側)は角270°×700
		200V	LGH-RN200RXVD-C	×	¥1,352,000	2,000m ³ /h	200.0m ²	1,030.0W	73.0%	65.0%	◎ 標準搭載	808mm	1,277mm	1,499mm	Φ250mm	○ 当社別売	接続パイプ(室外側)は角270°×700
	業務用ロスナイ天井埋込形 加温付	100V	LGH-N15RXK2	○ 障害内	¥190,000	150m ³ /h	15.0m ²	120.0W	74.0%	64.5%	○ 当社別売	288mm	888mm	769mm	Φ100mm	○ 当社別売	
		100V	LGH-N25RXK2	○ 障害内	¥208,000	250m ³ /h	25.0m ²	142.0W	70.0%	63.0%	○ 当社別売	288mm	908mm	894mm	Φ150mm	○ 当社別売	

設置 形態	タイプ名	電圧	形名	住宅用換気 システム 設計ソフト 対象機種※1	希望小売 価格 (税別)	風量(強)	対象 床面積 (目安)※2	消費電力	熱交換効率 ※3		CO2 センサー 対応可否 ※4	サイズ			接続 パイプ	アレル 除去 フィルター 対応可否	備考			
									温度	冷房(エンタルピー)		高さ	幅	奥行						
設備用ロスナイ		床置形	200V	LF-150X2-60	×	¥2,059,000	1,500m ³ /h	150m ³	1,210.0W	75.0%	65.0%	×	非対応	1,970mm	635mm	1,760mm	□300mm	×	非対応	
			200V	LF-150X2-F60	×	¥2,264,000	1,500m ³ /h	150m ³	1,210.0W	75.0%	65.0%	△	他社別売	1,970mm	635mm	1,760mm	□300mm	×	非対応	
			200V	LF-200X2-60	×	¥2,463,000	2,000m ³ /h	200m ³	1,850.0W	75.0%	65.0%	×	非対応	1,970mm	635mm	1,760mm	□300mm	×	非対応	
			200V	LF-200X2-F60	×	¥2,709,000	2,000m ³ /h	200m ³	1,850.0W	75.0%	65.0%	△	他社別売	1,970mm	635mm	1,760mm	□300mm	×	非対応	
			200V	LF-300X2-60	×	¥2,933,000	3,000m ³ /h	300m ³	2,500.0W	75.0%	65.0%	×	非対応	1,970mm	1,220mm	1,840mm	750×300mm	×	非対応	
			200V	LF-300X2-F60	×	¥3,226,000	3,000m ³ /h	300m ³	2,500.0W	75.0%	65.0%	△	他社別売	1,970mm	1,220mm	1,840mm	750×300mm	×	非対応	
			200V	LF-400X2-60	×	¥3,491,000	4,000m ³ /h	400m ³	3,000.0W	75.0%	65.0%	×	非対応	1,970mm	1,220mm	1,840mm	750×300mm	×	非対応	
			200V	LF-400X2-F60	×	¥3,841,000	4,000m ³ /h	400m ³	3,000.0W	75.0%	65.0%	△	他社別売	1,970mm	1,220mm	1,840mm	750×300mm	×	非対応	
			200V	LF-500X2-60	×	¥4,096,000	5,000m ³ /h	500m ³	3,560.0W	75.0%	65.0%	×	非対応	2,357mm	1,220mm	1,840mm	750×300mm	×	非対応	
			200V	LF-500X2-F60	×	¥4,506,000	5,000m ³ /h	500m ³	3,560.0W	75.0%	65.0%	△	他社別売	2,357mm	1,220mm	1,840mm	750×300mm	×	非対応	
		床置ビルトイン形加温付	200V	LB-150KX5-60	×	¥2,478,000	1,500m ³ /h	150m ³	1,500.0W	70.0%	67.0%	×	非対応	2,127mm	590mm	1,767mm	□352mm	×	非対応	
			200V	LB-200KX5-60	×	¥3,186,000	2,000m ³ /h	200m ³	2,100.0W	70.0%	67.0%	×	非対応	2,127mm	590mm	1,767mm	452×352mm	×	非対応	
			200V	LB-200KF8-60	×	オープン	1,500m ³ /h	150m ³	1,500.0W	70.0%	67.0%	×	非対応	2,127mm	590mm	1,825mm	□352mm	×	非対応	
			200V	LB-200KF8-60	×	オープン	2,000m ³ /h	200m ³	2,100.0W	70.0%	67.0%	×	非対応	2,127mm	590mm	1,825mm	452×352mm	×	非対応	
		外気処理ユニット	200V	LB-150KF8-60	×	オープン	1,500m ³ /h	150m ³	1,500.0W	70.0%	67.0%	×	非対応	2,127mm	590mm	1,825mm	□352mm	×	非対応	
			200V	LB-200KF8-60	×	オープン	2,000m ³ /h	200m ³	2,100.0W	70.0%	67.0%	×	非対応	2,127mm	590mm	1,825mm	452×352mm	×	非対応	
			200V	LPB-350KX3-K	×	¥6,458,000	3,500m ³ /h	350m ³	3,900.0W	77.0%	60.5%	△	他社別売	2,236mm	1,875mm	1,500mm	280×540mm	×	非対応	
			200V	LPB-500KX3-K	×	¥6,032,000	5,000m ³ /h	500m ³	6,200.0W	77.0%	60.5%	△	他社別売	2,336mm	1,975mm	1,690mm	280×720mm	×	非対応	
天井埋込 (ダクト取)		ビル用ロスナイバック形	200V	LP-250X4-60	×	¥3,765,000	2,500m ³ /h	250m ³	2,500.0W	77.0%	60.0%	△	他社別売	1,515mm	2,082mm	1,218mm	O.A.RA-420×1100mm SA.EA-420×640mm	×	非対応	
			200V	LP-500X4-60	×	¥4,782,000	5,000m ³ /h	500m ³	5,600.0W	77.0%	60.0%	△	他社別売	2,015mm	2,082mm	1,218mm	O.A.RA-420×1100mm SA.EA-420×640mm	×	非対応	
			200V	LP-750X4-60	×	¥6,224,000	7,500m ³ /h	750m ³	7,000.0W	77.0%	60.0%	△	他社別売	2,515mm	2,082mm	1,218mm	O.A.RA-420×1100mm SA.EA-420×640mm	×	非対応	
			200V	LP-1000X4-60	×	¥7,362,000	10,000m ³ /h	1,000m ³	11,100.0W	77.0%	60.0%	△	他社別売	3,015mm	2,082mm	1,218mm	O.A.RA-420×1100mm SA.EA-420×640mm	×	非対応	
			100V	VL-100ZSD2	○	¥74,800	87m ³ /h	8.7m ³	44.0W	63.0%	43.0%	△	他社別売	440mm	455mm	204mm	Φ100mm	○	当社別売	
			100V	VL-100ZSD3	○	¥82,300	87m ³ /h	8.7m ³	44.0W	63.0%	43.0%	△	他社別売	440mm	455mm	204mm	Φ100mm	◎	標準搭載	
			100V	VL-100ZSDK2	○	¥74,800	87m ³ /h	8.7m ³	44.0W	63.0%	43.0%	△	他社別売	440mm	455mm	204mm	Φ100mm	○	当社別売	
			100V	VL-100ZSDK3	○	¥82,300	87m ³ /h	8.7m ³	44.0W	63.0%	43.0%	△	他社別売	440mm	455mm	204mm	Φ100mm	◎	標準搭載	
			100V	VL-100ZSDK2-BR	○	¥74,800	100m ³ /h	10.0m ³	44.0W	63.0%	43.0%	△	他社別売	213mm	455mm	527mm	Φ100mm	○	当社別売	
			100V	VL-150ZSD2	○	¥126,500	130m ³ /h	13.0m ³	43.0W	62.0%	42.0%	△	他社別売	440mm	455mm	293mm	Φ100mm	○	当社別売	
		100V	VL-150ZSD3	○	¥139,200	130m ³ /h	13.0m ³	43.0W	62.0%	42.0%	△	他社別売	440mm	455mm	293mm	Φ100mm	◎	標準搭載		
		100V	VL-150ZSDK2	○	¥126,500	130m ³ /h	13.0m ³	43.0W	62.0%	42.0%	△	他社別売	440mm	455mm	293mm	Φ100mm	○	当社別売		
		100V	VL-150ZSDK3	○	¥139,200	130m ³ /h	13.0m ³	43.0W	62.0%	42.0%	△	他社別売	440mm	455mm	293mm	Φ100mm	◎	標準搭載		
		電気ランチャー 急速排気付 複力センサー付		電気ランチャー 急速排気付 複力センサー付	100V	VL-200ZSA2	△	局所換気	¥91,300	100m ³ /h	10.0m ³	23.0W	76.0%	58.0%	×	非対応	213mm	455mm	527mm	Φ100mm
100V	VL-200ZSA3				△	局所換気	¥100,500	100m ³ /h	10.0m ³	23.0W	76.0%	58.0%	×	非対応	213mm	455mm	527mm	Φ100mm	◎	標準搭載
100V	VL-200ZSDK2				○	¥80,300	48m ³ /h	4.8m ³	23.0W	76.0%	58.0%	△	他社別売	440mm	455mm	204mm	Φ100mm	○	当社別売	
100V	VL-200ZSDK3				○	¥88,300	48m ³ /h	4.8m ³	23.0W	76.0%	58.0%	△	他社別売	440mm	455mm	204mm	Φ100mm	◎	標準搭載	
100V	VL-200ZSDK2-BR				○	¥80,300	100m ³ /h	10.0m ³	23.0W	76.0%	58.0%	△	他社別売	213mm	455mm	527mm	Φ100mm	○	当社別売	
100V	VL-130ZS2				○	¥78,100	113m ³ /h	11.3m ³	39.0W	64.0%	44.0%	△	他社別売	440mm	455mm	293mm	Φ100mm	○	当社別売	
100V	VL-130ZS3				○	¥85,900	113m ³ /h	11.3m ³	39.0W	64.0%	44.0%	△	他社別売	440mm	455mm	293mm	Φ100mm	◎	標準搭載	
100V	VL-130ZSK2				○	¥78,100	113m ³ /h	11.3m ³	39.0W	64.0%	44.0%	△	他社別売	440mm	455mm	293mm	Φ100mm	○	当社別売	
100V	VL-130ZSK3				○	¥85,900	113m ³ /h	11.3m ³	39.0W	64.0%	44.0%	△	他社別売	440mm	455mm	293mm	Φ100mm	◎	標準搭載	
100V	VL-130ZSK2-BR				○	¥78,100	130m ³ /h	13.0m ³	39.0W	64.0%	44.0%	△	他社別売	302mm	455mm	527mm	Φ100mm	○	当社別売	
100V	VL-150ZS2			○	¥110,000	150m ³ /h	15.0m ³	43.0W	62.0%	42.0%	△	他社別売	302mm	455mm	527mm	Φ100mm	○	当社別売		
100V	VL-150ZS3			○	¥121,000	150m ³ /h	15.0m ³	43.0W	62.0%	42.0%	△	他社別売	302mm	455mm	527mm	Φ100mm	◎	標準搭載		
100V	VL-150ZSK2			○	¥110,000	150m ³ /h	15.0m ³	43.0W	62.0%	42.0%	△	他社別売	302mm	455mm	527mm	Φ100mm	○	当社別売		
100V	VL-150ZSK3			○	¥121,000	150m ³ /h	15.0m ³	43.0W	62.0%	42.0%	△	他社別売	302mm	455mm	527mm	Φ100mm	◎	標準搭載		
電気ランチャー無		電気ランチャー無	100V	VL-100ZS2	○	¥63,800	100m ³ /h	10.0m ³	44.0W	63.0%	43.0%	△	他社別売	213mm	455mm	527mm	Φ100mm	○	当社別売	
			100V	VL-100ZS3	○	¥70,200	100m ³ /h	10.0m ³	44.0W	63.0%	43.0%	△	他社別売	213mm	455mm	527mm	Φ100mm	◎	標準搭載	
			100V	VL-100ZSK2	○	¥63,800	100m ³ /h	10.0m ³	44.0W	63.0%	43.0%	△	他社別売	213mm	455mm	527mm	Φ100mm	○	当社別売	
			100V	VL-100ZSK3	○	¥70,200	100m ³ /h	10.0m ³	44.0W	63.0%	43.0%	△	他社別売	213mm	455mm	527mm	Φ100mm	◎	標準搭載	
			100V	VL-100ZSK2-BR	○	¥63,800	100m ³ /h	10.0m ³	44.0W	63.0%	43.0%	△	他社別売	213mm	455mm	527mm	Φ100mm	○	当社別売	
			100V	VL-130ZS2	○	¥78,100	113m ³ /h	11.3m ³	39.0W	64.0%	44.0%	△	他社別売	440mm	455mm	293mm	Φ100mm	○	当社別売	
			100V	VL-130ZS3	○	¥85,900	113m ³ /h	11.3m ³	39.0W	64.0%	44.0%	△	他社別売	440mm	455mm	293mm	Φ100mm	◎	標準搭載	
			100V	VL-130ZSK2	○	¥78,100	113m ³ /h	11.3m ³	39.0W	64.0%	44.0%	△	他社別売	440mm	455mm	293mm	Φ100mm	○	当社別売	
			100V	VL-130ZSK3	○	¥85,900	113m ³ /h	11.3m ³	39.0W	64.0%	44.0%	△	他社別売	440mm	455mm	293mm	Φ100mm	◎	標準搭載	
			100V	VL-130ZSK2-BR	○	¥78,100	130m ³ /h	13.0m ³	39.0W	64.0%	44.0%	△	他社別売	302mm	455mm	527mm	Φ100mm	○	当社別売	
		100V	VL-150ZS2	○	¥110,000	150m ³ /h	15.0m ³	43.0W	62.0%											

